

R-9110

C4 INSIDE BELT MOUNT INSTALLATION INSTRUCTIONS

The R-9110 inside belt mount has been designed to provide a mounting point for a snap in racing lap belt. Once the R-9110 inside belt mount is installed the lap belt can be removed and installed without removing the seat. The factory seat belt remains functional. The outside lap belt mounting point is provided with our R-1110 harness mount bar.

Step 1.

Remove (4) seat track to floor mounting bolts and move seat to gain access to the factory inside (tunnel side) seat belt mounting point. Remove factory-mounting bolt (this requires the use of a T-500 torx socket.)

Step 2.

Reinstall the bolt with the R-9110 belt mount placed between the factory seat belt and the tunnel.
See **Fig. 1**

Tip: When using the R-9110 belt mount in conjunction with the R-1110 harness mount bar you can substitute the slightly longer bolt that you removed from the shoulder strap "D" ring in place of the factory mounting bolt you removed.

Step 3.

Reinstall the seat by reversing Step 1.

Performance driving events are by nature potentially hazardous to your health. Brey-Krause Mfg. Co. Inc. shall not be liable for injury, consequential, or other types of damages resulting from the use or misuse of our products. Proper installation of these parts is critical and should only be done by a professional shop.

Fig. 1

