

**R-9521/R9522**

**ROLL BAR FIRE EXTINGUISHER MOUNT**  
**INSTALLATION INSTRUCTIONS**

Fits all cars with 1.5" or 40 mm (R-9521) or 1.75" (R-9522) roll bars

The R-9521 and R-9522 have been design to provide a secure way to mount a fire extinguisher directly to a roll bar. They can be used with either the standard fire extinguisher mount or the R-9520 Quick Release Mount.

Step 1

Remove lock nuts to separate two halves of the mount.

Step 2

Install the mount to the top plate of the R-9521/R-9522 with the supplied locking bolts.

Step 3

Locate where you would like to place the mount. It should be somewhere that can be easily reached from the seat while strapped in. It is recommended that the mount be installed lower than head level.

Hold the fire extinguisher up to the bar in the desired location to make sure it will not hit any other bars.

Step 4

Place a clamp half on either side of the bar, install small aluminum plate on the bottom of the insert and tighten the lock nuts. Make sure you tighten them evenly to prevent bending the plate.

Make sure that once the bolts are tightened that you can't rotate the mount.

The finished installation should look similar to below.



Performance driving events are by nature potentially hazardous to your health. Brey-Krause Mfg. Co. Inc. shall not be liable for injury, consequential, or other types of damages resulting from the use or misuse of our products. Proper installation of these parts is critical and should only be done by a professional shop.